

## EXEMPLES : SPOKE WIRE

**Description :** Round galvanised wire for spokes.

**Steel :** 0,30 to 0,60 % carbon.

**Tensite strenght :** 900 to 1 400 N/mm<sup>2</sup>.

**Coating :** - Electro-galvanised as per international standards.  
- Bright.

**Diameter :** 1,98 to 3,40 mm.

**Tolerances :** ± 0,01 to ± 0,03 mm according to wire diameter.

**Packaging :** - Reels from 400 to 1 400 Kg.  
- Orbit wound coils.



	REELS				ORBIT WOUND COILS
Type	RP 700	RP 1000	RP 1400	Type	PC
Weight of wire (Kg)	730	980	1400	Weight of wire (Kg)	500 / 1000
Ø Flange (mm)	750	1010	1010	Ø outside dia. (mm)	800
Ø Inside dia. (mm)	80	80	80	Ø inside dia. (mm)	350 / 400
Ø Core dia. (mm)	472	637	637		-
Height (mm)	702	539	699	Height (mm)	300 / 900

Please note all weights shown are approximate, and issued for guidance only. All measurement are metric.

**Unwinding :** Dynamic or static. Unwinding systems are available on request.

**Important characteristics :** It is recommended to specify the diameter of your wire requirements in mm.

CONFLANDEY reserves the right to modify any of the above details in the pursuit of improvements in quality and service.

## CONFLANDEY INDUSTRIES

3 RUE DU CHATEAU AMONCOURT - BP 21 70170 PORT SUR SAONE - FRANCE

Tél. : 33 (3) 84.91.38.38 - FAX : 33 (3) 84.91.47.04

[contact@conflandey-industries.com](mailto:contact@conflandey-industries.com)